Data Sheet

We make sure



SCALEOVIEW H19-2 19 Inch LCD Display

Issue June 2007

Pages 2

The SCALEOVIEW H19-2 is a display optimized for users looking for functionality in lifestyle design. With its sleek and space-saving look, this is the best choice LCD for home and office usage, and also in representative areas. It offers best performance as well as multimedia features for photo editing, gaming and watching the latest DVDs. Combined with the new features incorporated in the DisplayView™ technology this SCALEOVIEW display is the ideal companion for home, office and multimedia applications.

Highlights

- Best performance at an affordable price
 - Office applications
 - Internet and multimedia are supported best
- Very easy and comfortable to use
 - Plug & Play
 - Auto-adjust
 - Easy-to-use OSD menu

DisplayView™ technology

■ DisplayView[™] Speed:

Adjustable overdrive technology for best and optimized picture performance

■ DisplayView[™] Bright:

Color engine for optimized picture quality

■ DisplayView™ Clean:

Tidy desk with

- optimized cable conduct
- integrated USB port for comfortable connection of digital camera or memorystick
- integrated audio interface for comfortable connection of headset
- integrated pen tray for storage of pens, post its, etc.
- DisplayView™ Light:

Adjustable desk light above pen tray for better sight on your desk

Ergonomics

- Optimum flicker-free and distortion-free ergonomics
- Excellent color purity
- Well balanced brightness uniformity
- Excellent high contrast
- Space saving design
- Fast response times 5 ms (2 ms gtg)

Technical highlights

■ 19" (48 cm) LCD Display

■ Excellent contrast 1000:1 (typ.)

2500:1 (advanced)

■ Brightness 300 cd/m² (typ.)
■ Response time 5 ms (typ), 2 ms gtg

■ Viewing angle 160° / 160°

■ Video input 1 x D-Sub, 1 x DVI-I

■ Audio connectors
 ■ USB connector
 ■ DisplayViewTM Light
 for microphone and headset for camera / memorystick adjustable desk light

Reliability

- Low power consumption
- Power Management according EPA
- Guaranteed quality and stability











Visible screen diagonal	19 inch (48 cm)
Resolutions	
Pixels	1280 x 1024
Pixels*	1024 x 768
Pixels*	800 x 600
* expanded	
Picture size	372.3 x 301 mm
Colors	16.2 million
Pixel Pitch	0.294 mm
Frequencies	
Horizontal	31 - 81 kHz
Vertical	56 - 75 Hz
Brightness (typical)	300 cd/m ²
Contrast (typical)	1000:1
(advanced)	2500:1
Viewing angle (typical)	
Horizontal	160°
Vertical	160°
Response time (typical)	5 ms
Grey to grey	2 ms with active over drive
Plug and Play	VESA DDC2B
Setting options Power on/off, Auto Adjust, Br Phase, Sharpness, Color Cor OSD Time out, Factory recall Mode Control for different pic	ntrol., OSD Position, , Information, Volume Control,
OSD Language English, German, Spanish, Foundard Swedish, Dutch	rench, Italian, Russian,
Base	
Tilt angle	-5° / +20°
Video input	1 x D-SUB
	1 x DVI-I
Audio input / output	
Audio signal input	3.5 mm stereo phone jack
Audio output	2 W (L) + 2 W (R)

Electrical values (external pov	wer adapter)	
Rated voltage	100 - 240 V	
Frequency	47 - 63 Hz	
Power draw		
Max.	50 W	
Stand by	2 W	
Protection class	1	
Temperatures/ dimensions/ weight		
Ambient temperature (to IEC72		
Working (recommended)	15°C to 32°C	
Storage	-20°C to 60°C	
Dimensions (H x W x D):	440 × 447 × 400 F	
(with stand) Weight (Monitor only):	449 x 417 x 189.5 mm 5.1 kg	
	3.1 kg	
Reliability	70 000 b	
MTBF (demonstrated) Lifetime of LCD backlight	70,000 h 50,000 h	
(brightness > 50 % of original b		
· · · · · · · · · · · · · · · · · · ·	originaless)	
Compliance with standards	EN60950	
Product safety Ergonomics	GS mark	
Ligonomics	ISO13406-2	
	(Pixel fault class II)	
Radiation immunity and	CE certification according	
RFI suppression	to EC Directive	
	89/336/EEC	
	(EN55022/B, EN55024,	
	EN61000-3-2/-3);	
	TCO'03	
Delivered accessories		
External power adapter		
Power cable (1.8 m)	For wall socket	
-	(Euro-Schuko-Type CEE7)	
Data cable (1.8 m)*	D-SUB (15-pin)	
Data cable (1.8 m)*	DVI-D	
USB cable (1.8 m)* Audio cable (1.8 m)*	USB-A to USB-B 1x microphone, 1x speaker	
* detachable on display	1x microphone, 1x speaker	
	Otan dandina dan aras satina	
Special features	Standardized mounting	
	interface according VESA FPMPMI (100 mm)	
	Kensington Lock	
	Adjustable blue desk light	
	Removable pen tray	
	Removable back cover	
	Cable loop	
	Loop through USB	
	connector	
	Loop through headset	
	connector	
Order code	S26361-K1183-V170	
EAN	4333643007959	