



SPEC® CFP2006 Result

Copyright ©2007 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp®_rate2006 = 55.7

CELSIUS R650, Intel Xeon X5260, 3.33 GHz

SPECfp_rate_base2006 = 50.4

CPU2006 license: 22


Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Feb-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon X5260
 CPU Characteristics: 3333
 CPU MHz: Integrated
 FPU: 4 cores, 2 chips, 2 cores/chip
 CPU(s) enabled: 1,2 chips
 CPU(s) orderable: 32 KB I + 32 KB D on chip per core
 Primary Cache: 6 MB I+D on chip per chip
 Secondary Cache:

Continued on next page

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP1,
 Kernel 2.6.16.46-0.12-smp
 Compiler: Intel C++ and Fortran Compiler
 for Linux32 and Linux64
 Version 10.1 - Build 20070725
 Auto Parallel: Yes
 File System: ext3
 System State: Multi-User, Run Level 3
 Base Pointers: 64-bit

Continued on next page



SPEC CFP2006 Result

Copyright ©2007 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp_rate2006 = 55.7

CELSIUS R650, Intel Xeon X5260, 3.33 GHz

SPECfp_rate_base2006 = 50.4

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Feb-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

Hardware (Continued)

L3 Cache: None
Other Cache: None
Memory: 8 GB (8x1 GB PC2-5300F, 2 rank, CL5-5-5, ECC)
Disk Subsystem: 1 x SATA II, 400 GB, 7200 rpm
Other Hardware: None

Software (Continued)

Peak Pointers: 32/64-bit
Other Software: binutils-2.17.50.0.5-0.1.x86_64

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	<u>1499</u>	<u>36.3</u>	1497	36.3	1499	36.3	4	<u>1451</u>	<u>37.5</u>	1449	37.5	1452	37.4
416.gamess	4	797	98.2	800	97.9	<u>798</u>	<u>98.2</u>	4	789	99.3	<u>788</u>	<u>99.4</u>	788	99.4
433.milc	4	1537	23.9	<u>1537</u>	<u>23.9</u>	1539	23.9	4	1544	23.8	<u>1545</u>	<u>23.8</u>	1548	23.7
434.zeusmp	4	673	54.1	673	54.1	<u>673</u>	<u>54.1</u>	4	665	54.7	662	55.0	<u>663</u>	<u>54.9</u>
435.gromacs	4	<u>338</u>	<u>84.4</u>	339	84.2	338	84.5	4	334	85.5	<u>335</u>	<u>85.3</u>	335	85.2
436.cactusADM	4	890	53.7	<u>884</u>	<u>54.1</u>	883	54.1	1	179	66.9	<u>179</u>	<u>66.7</u>	181	66.0
437.leslie3d	4	<u>1378</u>	<u>27.3</u>	1378	27.3	1375	27.3	4	<u>1277</u>	<u>29.5</u>	1273	29.5	1278	29.4
444.namd	4	<u>457</u>	<u>70.1</u>	458	70.1	457	70.3	4	454	70.7	<u>455</u>	<u>70.5</u>	458	70.0
447.dealII	4	493	92.9	<u>492</u>	<u>92.9</u>	492	93.0	4	475	96.2	473	96.7	<u>474</u>	<u>96.6</u>
450.soplex	4	1060	31.5	<u>1064</u>	<u>31.4</u>	1064	31.4	4	942	35.4	947	35.2	<u>945</u>	<u>35.3</u>
453.povray	4	<u>191</u>	<u>112</u>	192	111	189	113	4	162	132	<u>162</u>	<u>132</u>	162	131
454.calculix	4	484	68.1	488	67.7	<u>487</u>	<u>67.8</u>	4	341	96.8	345	95.5	<u>342</u>	<u>96.4</u>
459.GemsFDTD	4	1608	26.4	<u>1598</u>	<u>26.6</u>	1593	26.6	4	1515	28.0	1502	28.3	<u>1504</u>	<u>28.2</u>
465.tonto	4	495	79.6	496	79.4	<u>495</u>	<u>79.5</u>	4	<u>483</u>	<u>81.5</u>	483	81.4	482	81.6
470.lbm	4	2859	19.2	2859	19.2	<u>2859</u>	<u>19.2</u>	4	1751	31.4	<u>1751</u>	<u>31.4</u>	1750	31.4
481.wrf	4	<u>867</u>	<u>51.5</u>	868	51.5	867	51.6	4	868	51.5	<u>868</u>	<u>51.5</u>	867	51.6
482.sphinx3	4	1627	47.9	<u>1632</u>	<u>47.8</u>	1636	47.7	4	1476	52.8	<u>1487</u>	<u>52.4</u>	1493	52.2

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
OMP_NUM_THREADS set to number of cores (default)

Platform Notes

BIOS configuration:
Enhanced Speedstep Technology = Disable
Hardware Prefetch = Enable, Adjacent Sector Prefetch = Enable
SnoopFilter = Enable



SPEC CFP2006 Result

Copyright ©2007 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp_rate2006 = 55.7

CELSIUS R650, Intel Xeon X5260, 3.33 GHz

SPECfp_rate_base2006 = 50.4

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Feb-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

General Notes

All binaries were built with 64-bit Intel compiler except:
437.leslie3d, 450.soplex, 470.lbm, and 482.sphinx3 in peak
were built with 32-bit Intel compiler by changing
the path for include and library files.

All binaries were built with 64-bit Intel compiler except:
450.soplex, 470.lbm and 482.sphinx3 in peak were built with
32-bit Intel compiler by changing the path for include and library files.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64



SPEC CFP2006 Result

Copyright ©2007 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp_rate2006 = 55.7

CELSIUS R650, Intel Xeon X5260, 3.33 GHz

SPECfp_rate_base2006 = 50.4

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Feb-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

Base Optimization Flags

C benchmarks:

-fast

C++ benchmarks:

-fast

Fortran benchmarks:

-fast

Benchmarks using both Fortran and C:

-fast

Peak Compiler Invocation

C benchmarks (except as noted below):

/opt/intel/cc/10.1.008/bin/icc -L/opt/intel/cc/10.1.008/lib
-I/opt/intel/cc/10.1.008/include

433.milc: icc

C++ benchmarks (except as noted below):

icpc

450.soplex: /opt/intel/cc/10.1.008/bin/icpc -L/opt/intel/cc/10.1.008/lib
-I/opt/intel/cc/10.1.008/include

Fortran benchmarks (except as noted below):

ifort

437.leslie3d: /opt/intel/fc/10.1.008/bin/ifort -L/opt/intel/fc/10.1.008/lib
-I/opt/intel/fc/10.1.008/include

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64

Continued on next page



SPEC CFP2006 Result

Copyright ©2007 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp_rate2006 = 55.7

CELSIUS R650, Intel Xeon X5260, 3.33 GHz

SPECfp_rate_base2006 = 50.4

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Feb-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

Peak Portability Flags (Continued)

453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-scalar-rep- -prefetch -opt-malloc-options=3

482.sphinx3: -fast -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4
-ansi-alias

Fortran benchmarks:

410.bwaves: -fast -prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-opt-malloc-options=3

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-prefetch

Continued on next page



SPEC CFP2006 Result

Copyright ©2007 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp_rate2006 = 55.7

CELSIUS R650, Intel Xeon X5260, 3.33 GHz

SPECfp_rate_base2006 = 50.4

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Feb-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

Peak Optimization Flags (Continued)

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/flags-ic101-linux-intel64.20080305.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/flags-ic101-linux-intel64.20080305.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Wed Mar 5 13:56:44 2008 by SPEC CPU2006 PS/PDF formatter v5614.