



SPEC® CFP2006 Result

Copyright ©2007 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp®_rate2006 = 45.8

CELSIUS M460, Intel Core 2 Quad Q9550

SPECfp_rate_base2006 = 43.3

CPU2006 license: 22


Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Mar-2008

Hardware Availability: Mar-2008

Software Availability: Nov-2007



Hardware

CPU Name: Intel Core 2 Quad Q9550
CPU Characteristics: 2833
CPU MHz: Integrated
FPU: 4 cores, 1 chip, 4 cores/chip
CPU(s) enabled: 1 chip
CPU(s) orderable: 32 KB I + 32 KB D on chip per core
Primary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores
Secondary Cache:

Continued on next page

Software

Operating System: Windows Vista Ultimate, 64 bit Version

Continued on next page



SPEC CFP2006 Result

Copyright ©2007 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp_rate2006 = 45.8

CELSIUS M460, Intel Core 2 Quad Q9550

SPECfp_rate_base2006 = 43.3

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Mar-2008

Hardware Availability: Mar-2008

Software Availability: Nov-2007

Hardware (Continued)

L3 Cache: None
 Other Cache: None
 Memory: 4 GB (4x1 GB PC2-6400 CL6 SDRAM)
 Disk Subsystem: 1 x 400 GB SATA 7200 RPM
 Other Hardware: None

Software (Continued)

Compiler: Intel C++ Compiler
 for applications running on Intel 64,
 Version 10.1, Build 20070913
 Intel Visual Fortran Compiler
 for applications running on Intel 64,
 Version 10.1, Build 20070913
 Microsoft Visual Studio 2005 with SP1
 (for libraries)
 Auto Parallel: No
 File System: NTFS
 System State: Default
 Base Pointers: 64-bit
 Peak Pointers: 64-bit
 Other Software: SmartHeap Library Version 8.0 (64 bit) from
<http://www.microquill.com/>

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	<u>1760</u>	<u>30.9</u>	1755	31.0	1783	30.5	4	1764	30.8	<u>1788</u>	<u>30.4</u>	1800	30.2
416.gamess	4	970	80.7	<u>971</u>	<u>80.7</u>	976	80.2	4	970	80.7	<u>971</u>	<u>80.7</u>	976	80.2
433.milc	4	2012	18.3	<u>2014</u>	<u>18.2</u>	2017	18.2	4	1904	19.3	1899	19.3	<u>1900</u>	<u>19.3</u>
434.zeusmp	4	<u>657</u>	<u>55.4</u>	661	55.1	653	55.8	4	637	57.1	<u>630</u>	<u>57.7</u>	630	57.8
435.gromacs	4	385	74.1	<u>386</u>	<u>74.0</u>	389	73.5	4	<u>386</u>	<u>74.0</u>	386	74.0	385	74.1
436.cactusADM	4	814	58.7	<u>814</u>	<u>58.7</u>	816	58.6	4	773	61.9	<u>768</u>	<u>62.2</u>	768	62.3
437.leslie3d	4	1684	22.3	1684	22.3	<u>1684</u>	<u>22.3</u>	4	1683	22.3	1687	22.3	<u>1685</u>	<u>22.3</u>
444.namd	4	545	58.8	<u>549</u>	<u>58.4</u>	551	58.2	4	537	59.7	<u>537</u>	<u>59.7</u>	538	59.6
447.dealII	4	<u>749</u>	<u>61.1</u>	755	60.6	740	61.9	4	<u>709</u>	<u>64.5</u>	712	64.3	705	64.9
450.soplex	4	1279	26.1	1255	26.6	<u>1268</u>	<u>26.3</u>	4	<u>1279</u>	<u>26.1</u>	1287	25.9	1278	26.1
453.povray	4	247	86.2	251	84.9	<u>249</u>	<u>85.4</u>	4	205	104	<u>205</u>	<u>104</u>	205	104
454.calculix	4	<u>582</u>	<u>56.7</u>	588	56.1	581	56.8	4	388	85.1	<u>388</u>	<u>85.0</u>	388	85.0
459.GemsFDTD	4	2128	19.9	2141	19.8	<u>2130</u>	<u>19.9</u>	4	2054	20.7	<u>2054</u>	<u>20.7</u>	2051	20.7
465.tonto	4	<u>596</u>	<u>66.1</u>	596	66.0	592	66.5	4	<u>596</u>	<u>66.1</u>	596	66.0	592	66.5
470.lbm	4	2601	21.1	2608	21.1	<u>2606</u>	<u>21.1</u>	1	572	24.0	570	24.1	<u>570</u>	<u>24.1</u>
481.wrf	4	1041	42.9	<u>1036</u>	<u>43.1</u>	1035	43.2	4	1041	42.9	<u>1036</u>	<u>43.1</u>	1035	43.2
482.sphinx3	4	1583	49.2	<u>1587</u>	<u>49.1</u>	1588	49.1	4	1583	49.2	<u>1587</u>	<u>49.1</u>	1588	49.1

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

BIOS default settings have been used.



SPEC CFP2006 Result

Copyright ©2007 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp_rate2006 = 45.8

CELSIUS M460, Intel Core 2 Quad Q9550

SPECfp_rate_base2006 = 43.3

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Mar-2008

Hardware Availability: Mar-2008

Software Availability: Nov-2007

General Notes

For information about Fujitsu Siemens Computers please see:
<http://www.fujitsu-siemens.com/>

Compiler Invocation

C benchmarks:
icl -Qvc8 -Qc99

C++ benchmarks:
icl -Qvc8

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icl -Qvc8 -Qc99 ifort

Portability Flags

410.bwaves: -DSPEC_CPU_P64
416.gamess: -DSPEC_CPU_P64
433.milc: -DSPEC_CPU_P64
434.zeusmp: -DSPEC_CPU_P64
435.gromacs: -DSPEC_CPU_P64
436.cactusADM: -DSPEC_CPU_P64 -Qlowercase -assume:underscore
437.leslie3d: -DSPEC_CPU_P64
444.namd: -DSPEC_CPU_P64 -TP
447.dealII: -DSPEC_CPU_P64 -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
450.soplex: -DSPEC_CPU_P64
453.povray: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
454.calculix: -DSPEC_CPU_P64 -DSPEC_CPU_NOZMODIFIER -Qlowercase
459.GemsFDTD: -DSPEC_CPU_P64
465.tonto: -DSPEC_CPU_P64
470.lbm: -DSPEC_CPU_P64
481.wrf: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
482.sphinx3: -DSPEC_CPU_P64

Base Optimization Flags

C benchmarks:
-fast -F950000000 shlw64M.lib

C++ benchmarks:
-fast -Qcxx-features -F950000000 shlw64M.lib

Continued on next page



SPEC CFP2006 Result

Copyright ©2007 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp_rate2006 = 45.8

CELSIUS M460, Intel Core 2 Quad Q9550

SPECfp_rate_base2006 = 43.3

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Mar-2008

Hardware Availability: Mar-2008

Software Availability: Nov-2007

Base Optimization Flags (Continued)

Fortran benchmarks:

-fast -F950000000

Benchmarks using both Fortran and C:

-fast -F950000000

Peak Optimization Flags

C benchmarks:

433.milc: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -F950000000

470.lbm: -fast -Qunroll2 -Qscalar-rep- -Qprefetch -F950000000

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: -fast -Oa -F950000000 shlw64M.lib

447.dealII: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qcxx-features
-F950000000

450.soplex: Same as 447.dealII

453.povray: Same as 447.dealII

Fortran benchmarks:

410.bwaves: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -F950000000

416.gamess: basepeak = yes

434.zeusmp: -QXT -O2 -Qprec-div- -Qunroll10 -Qscalar-rep- -F950000000

437.leslie3d: Same as 410.bwaves

459.GemsFDTD: -fast -Qunroll2 -Ob0 -Qprefetch -F950000000

465.tonto: basepeak = yes

Benchmarks using both Fortran and C:

435.gromacs: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -F950000000

436.cactusADM: -fast -Qunroll2 -Qprefetch -F950000000

Continued on next page



SPEC CFP2006 Result

Copyright ©2007 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp_rate2006 = 45.8

CELSIUS M460, Intel Core 2 Quad Q9550

SPECfp_rate_base2006 = 43.3

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Mar-2008

Hardware Availability: Mar-2008

Software Availability: Nov-2007

Peak Optimization Flags (Continued)

454.calculix: -fast -Qunroll-aggressive -F950000000

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/CPU2006_flags.20080124.00.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/CPU2006_flags.20080124.00.xml

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Thu Apr 3 18:44:04 2008 by SPEC CPU2006 PS/PDF formatter v5614.